

S 300 **6 000**

wyłączniki nadprądowe S 303, S 304
charakterystyka B i C



6055 54



6056 53



6055 75



6056 73




Wymiary (str. 354)
Dane techniczne (str. 354)
Charakterystyki (str. 358)

Zdolność zwarciova:

6 000 EN 60898

Pak.	Nr ref.	Trójbiegunowe 400 V \sim		
		Prąd znamionowy I_n	Szerokość w modułach 17,5 mm	Produkt
		Charakterystyka B		
4/24	6055 46	6 A	3	S 303 B-6
1/18	6055 47	8 A	3	S 303 B-8
4/24	6055 48	10 A	3	S 303 B-10
1/18	6055 49	13 A	3	S 303 B-13
4/24	6055 50	16 A	3	S 303 B-16
4/24	6055 51	20 A	3	S 303 B-20
4/24	6055 52	25 A	3	S 303 B-25
4/24	6055 53	32 A	3	S 303 B-32
1/18	6055 54	40 A	3	S 303 B-40
1/18	6055 55	50 A	3	S 303 B-50
1/18	6055 56	63 A	3	S 303 B-63
		Charakterystyka C		
1/18	6056 40	0,3 A	3	S 303 C-0,3
1/18	6056 41	0,5 A	3	S 303 C-0,5
1/18	6056 42	1 A	3	S 303 C-1
1/18	6056 43	2 A	3	S 303 C-2
1/18	6056 44	3 A	3	S 303 C-3
1/18	6056 45	4 A	3	S 303 C-4
4/24	6056 46	6 A	3	S 303 C-6
1/18	6056 47	8 A	3	S 303 C-8
4/24	6056 48	10 A	3	S 303 C-10
1/18	6056 49	13 A	3	S 303 C-13
4/24	6056 50	16 A	3	S 303 C-16
4/24	6056 51	20 A	3	S 303 C-20
4/24	6056 52	25 A	3	S 303 C-25
4/24	6056 53	32 A	3	S 303 C-32
1/18	6056 54	40 A	3	S 303 C-40
1/18	6056 55	50 A	3	S 303 C-50
1/18	6056 56	63 A	3	S 303 C-63

Pak.	Nr ref.	Czterobiegunowe 400 V \sim		
		Prąd znamionowy I_n	Szerokość w modułach 17,5 mm	Produkt
		Charakterystyka B		
3/18	6055 66	6 A	4	S 304 B-6
3/18	6055 68	10 A	4	S 304 B-10
3/18	6055 70	16 A	4	S 304 B-16
3/18	6055 71	20 A	4	S 304 B-20
3/18	6055 72	25 A	4	S 304 B-25
3/18	6055 73	32 A	4	S 304 B-32
1/12	6055 74	40 A	4	S 304 B-40
1/12	6055 75	50 A	4	S 304 B-50
1/12	6055 76	63 A	4	S 304 B-63
		Charakterystyka C		
1/12	6056 60	0,3 A	4	S 304 C-0,3
1/12	6056 61	0,5 A	4	S 304 C-0,5
1/12	6056 62	1 A	4	S 304 C-1
1/12	6056 63	2 A	4	S 304 C-2
1/12	6056 65	4 A	4	S 304 C-4
3/18	6056 66	6 A	4	S 304 C-6
1/12	6056 67	8 A	4	S 304 C-8
3/18	6056 68	10 A	4	S 304 C-10
1/12	6056 69	13 A	4	S 304 C-13
3/18	6056 70	16 A	4	S 304 C-16
3/18	6056 71	20 A	4	S 304 C-20
3/18	6056 72	25 A	4	S 304 C-25
3/18	6056 73	32 A	4	S 304 C-32
1/12	6056 74	40 A	4	S 304 C-40
1/12	6056 75	50 A	4	S 304 C-50
1/12	6056 76	63 A	4	S 304 C-63



Wyłączniki nadprądowe S 300,
charakterystyka D

str. 353